

# PCA-M-HA R32 Stainless Steel Ceiling Suspended System

## Power Inverter Heat Pump (Single Phase)



The **PCA-M-HA** series is a ceiling suspended unit ideal for use in kitchen environments. The external casing is made of durable stainless steel that is resistant to oil and smoke, ensuring that the unit can be easily cleaned at all times. Our Power Inverter Heat Pump offers customers high seasonal efficiency, advanced control options and quiet operation, whilst providing greater flexibility and ease of installation.

### Key Features

- High performance oil mist filter
- Easy maintenance - fan casing can be separated into different sections allowing easy cleaning and the drain pan can also be cleaned easily on-site as the pipe connector can be quickly removed
- Optional decoration covers
- Durable stainless steel casing

PCA-M-HA - INDOOR UNIT		PCA-M71HA
CAPACITY (kW)	Heating (nominal) Cooling (nominal) Heating (UK) Cooling (UK)	7.6 (3.5-10.2) 7.1 (3.3-8.1) 6.8 (3.0-8.65) 6.55 (3.05-7.45)
SHF (nominal)		0.74
COP / EER (nominal)		3.50 / 3.51
SCOP / SEER		3.9 / 5.6
ENERGY EFFICIENCY CLASS	Heating/Cooling	A / A+
AIRFLOW (l/s)	Lo-Hi	267-300
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Hi	37-39
SOUND POWER LEVEL (dBA)		57
DIMENSIONS (mm)	Width x Depth x Height	1136 x 650 x 280
WEIGHT (kg)		42
ELECTRICAL SUPPLY		Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6
INTERCONNECTING CABLE No. Cores		4
WIRED REMOTE CONTROLLER REFERENCE		PAR-40MAA
WIRELESS REMOTE CONTROLLER REFERENCE		PAR-SL94B

PUZ-ZM - OUTDOOR UNIT		PUZ-ZM71VHAR1
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	49 / 47
SOUND POWER LEVEL (dBA)	Cooling	67
WEIGHT (kg)		70
DIMENSIONS (mm)	Width x Depth x Height	950 x 330 + 30 x 943
ELECTRICAL SUPPLY		220-240v, 50Hz
PHASE		Single
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal) Heating/Cooling (UK)	1.82 / 1.65 1.69 / 1.39
STARTING CURRENT (A)		6.0
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	7.5 / 6.7 [19.4]
FUSE RATING (BS88) - HRC (A)		25
MAINS CABLE No. Cores		3
MAX PIPE LENGTH (m)		55
MAX HEIGHT DIFFERENCE (m)		30
CHARGE REFRIGERANT (kg) / CO <sub>2</sub> EQUIVALENT (t) R32 (GWP 675) - 30m		2.80 / 1.89
MAX ADDITIONAL REFRIGERANT (kg) / CO <sub>2</sub> EQUIVALENT (t) R32 (GWP 675)		0.80 / 0.54