

PLA-SM R32 4-Way Blow Ceiling Cassette System

Inverter Heat Pump

Our **PLA-SM Inverter** range offers customers all the features and benefits of inverter technology whilst being cost effective.

Key Features

- Inverter cassette range only
- Single combination only
- Up to 40m pipe run
- Cost effective with the benefits and features of inverter technology
- Filter lowering operation down to 4m (optional PLP-6EAJ grille required)



PLA-SM INDOOR UNITS		PLA-SM71EA	PLA-SM100EA	PLA-SM100EA	PLA-SM125EA	PLA-SM125EA	PLA-SM140EA	PLA-SM140EA
CAPACITY (kW)	Heating (nominal)	8.0 (2.2-8.1)	11.2 (2.8-12.5)	11.2 (2.8-12.5)	13.5 (4.1-15.0)	13.5 (4.1-15.0)	15.0 (4.2-15.8)	15.0 (4.2-15.8)
	Cooling (nominal)	7.1 (2.2-8.1)	9.5 (4.0-10.6)	9.5 (4.0-10.6)	12.1 (5.8-13.0)	12.1 (5.8-13.0)	13.4 (5.8-14.1)	13.4 (5.8-14.1)
	Heating (UK)	6.80 (1.87-6.89)	9.63 (2.41-10.75)	9.63 (2.41-10.75)	11.61 (3.53-12.90)	11.61 (3.53-12.90)	12.90 (3.61-13.59)	12.90 (3.61-13.59)
	Cooling (UK)	6.53 (2.03-7.45)	8.55 (3.60-11.25)	8.55 (3.60-11.25)	10.89 (5.22-11.70)	10.89 (5.22-11.70)	11.61 (5.22-12.69)	11.61 (5.22-12.69)
SHF (nominal)		0.75	0.77	0.77	0.73	0.73	0.70	0.70
COP / EER (nominal)		3.50 / 3.60	3.61 / 3.40	3.61 / 3.40	3.61 / 2.90	3.61 / 2.90	3.30 / 2.61	3.30 / 2.61
SCOP (ηsh) / SEER (ηsc) (BS EN14825)		3.90 / 6.00	4.50 / 6.00	4.50 / 6.00	3.9 (154.1%) / 5.5 (225.2%)	3.9 (154.1%) / 5.5 (225.2%)	3.9 (153.3%) / 5.5 (224.9%)	3.9 (153.3%) / 5.5 (224.9%)
ErP ENERGY EFFICIENCY CLASS Heating/Cooling		A / A+	A+ / A+	A+ / A+	A / A	A / A	A / A	A / A
AIRFLOW (l/s)	Lo-Mi1-Mi2-Hi	233-283-317-350	317-383-433-483	317-383-433-483	350-417-467-517	350-417-467-517	400-433-483-533	400-433-483-533
PIPE SIZE mm (in)	Gas/Liquid	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")	15.88 (5/8") / 9.52 (3/8")
SOUND PRESSURE LEVEL (dBA)	Lo-Mi1-Mi2-Hi	28-30-32-34	31-34-37-40	31-34-37-40	33-37-41-44	33-37-41-44	36-39-42-44	36-39-42-44
SOUND POWER LEVEL (dBA)		56	61	61	65	65	65	65
DIMENSIONS (mm)	Width x Depth x Height (Grille)	840 (950) x 840 (950) x 258 (40)	840 (950) x 840 (950) x 298 (40)	840 (950) x 840 (950) x 298 (40)	840 (950) x 840 (950) x 298 (40)	840 (950) x 840 (950) x 298 (40)	840 (950) x 840 (950) x 298 (40)	840 (950) x 840 (950) x 298 (40)
WEIGHT (kg)	Unit / Panel	21 (5)	24 (5)	24 (5)	26 (5)	26 (5)	26 (5)	26 (5)
ELECTRICAL SUPPLY		Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit	Fed by Outdoor Unit
FUSE RATING (BS88) - HRC (A)		6	6	6	6	6	6	6
INTERCONNECTING CABLE No. Cores		4	4	4	4	4	4	4
GRILLE REFERENCE		PLP-6EA	PLP-6EA	PLP-6EA	PLP-6EA	PLP-6EA	PLP-6EA	PLP-6EA
WIRED REMOTE CONTROLLER REFERENCE		PAR-40MAA	PAR-40MAA	PAR-40MAA	PAR-40MAA	PAR-40MAA	PAR-40MAA	PAR-40MAA
WIRELESS REMOTE CONTROLLER REFERENCE		PAR-SL100A-E	PAR-SL100A-E	PAR-SL100A-E	PAR-SL100A-E	PAR-SL100A-E	PAR-SL100A-E	PAR-SL100A-E

SUZ-SM / PUZ-SM OUTDOOR UNITS		SUZ-SM71VA	PUZ-SM100VKA	PUZ-SM100YKA	PUZ-SM125VKA	PUZ-SM125YKA	PUZ-SM140VKA	PUZ-SM140YKA
SOUND PRESSURE LEVEL (dBA)	Heating/Cooling	51 / 49	54 / 51	54 / 51	56 / 54	56 / 54	57 / 55	57 / 55
SOUND POWER LEVEL (dBA)	Cooling	66	70	70	72	72	73	73
WEIGHT (kg)		55	76	78	84	85	84	85
DIMENSIONS (mm)	Width x Depth x Height	840 x 330 x 880	1050 x 330 x 981	1050 x 330 x 981	1050 x 330 x 981	1050 x 330 x 981	1050 x 330 x 981	1050 x 330 x 981
ELECTRICAL SUPPLY		220-240v, 50Hz	220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz	380-415v, 50Hz
PHASE		Single	Single	Three	Single	Three	Single	Three
SYSTEM POWER INPUT (kW)	Heating/Cooling (nominal)	2.28 / 1.97	3.10 / 2.79	3.10 / 2.79	3.73 / 4.17	3.73 / 4.17	4.54 / 5.13	4.54 / 5.13
	Heating/Cooling (UK)	1.94 / 1.70	2.64 / 2.40	2.64 / 2.40	3.17 / 3.59	3.17 / 3.59	3.87 / 4.14	3.87 / 4.14
STARTING CURRENT (A)		9.7	13.4	4.8	17.4	6.3	22.3	8.1
SYSTEM RUNNING CURRENT (A)	Heating/Cooling [MAX]	9.7 / 8.3 [14.8]	13.4 / 12.1 [20.0]	4.8 / 4.3 [11.5]	15.6 / 17.4 [26.5]	5.6 / 6.3 [11.5]	19.0 / 22.3 [30.0]	6.9 / 8.1 [11.5]
FUSE RATING (BS88) - HRC (A)		20	32	16	32	16	40	16
MAINS CABLE No. Cores		3	3	5	3	5	3	5
MAX PIPE LENGTH (m)		30	30	30	40	40	40	40
MAX HEIGHT DIFFERENCE (m)		30	30	30	30	30	30	30
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t)	R32 (GWP 675)	1.45 / 0.98 (7m)	3.10 / 2.09 (30m)	3.10 / 2.09 (30m)	3.60 / 2.43 (30m)	3.60 / 2.43 (30m)	3.60 / 2.43 (30m)	3.60 / 2.43 (30m)
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t)	R32 (GWP 675)	2.37 / 1.80	N/A	3.50 / 2.36	4.00 / 2.70	4.00 / 2.70	4.00 / 2.70	4.00 / 2.70

Note: The PLP-6EAE 3D i-See sensor grille or PAC-SE1ME-E corner panel will NOT operate with this model.